

CPU SERIES -Aspera Technical Data

Technical Data

Unit Model	Compressor Details				Condenser Details				Receiver Cap	Consections Solder		Dimensions (mm)			
	Model	Disp	Phase	F.L.A	L.R.A	No. Fans	ROW	TUBES		Liquid	Suction	Lth	Dth	Ht	
CPUNB6144Z	NB6144Z	5.9	1 PH	1.7	7.5										
CPUNEK6165GK	NE6165GK	6.05	1PH			1 X254	3	11					340	296	465
CPUNE6181GK	NE6181GK	7.28	1PH	3.5	9.7	1 X 254	3	11	1 kg		1/4	3/8	340	296	465
CPUNE6210GK	NE6210GK	8.78	1 PH	3.8	14	1 X 254	3	11			1/4	3/8	340	396	465
CPUNE6170Z	NE6170Z	8.9	1 PH	2.4	9.7										
CPUNE6187Z	NE6187Z	12	1 PH	3.4	14										
CPUT6213Z	NT6213Z	17.4	1 PH	4.5	20.4										
CPUNE9213GK	NE9213GK	12.12	1 PH	3.9	13.3	1 X 254	4	15	2.3kg		3/8	3/8	340	396	505
CPUNE9213GK/2	NE9213GK	12.12	1 PH	3.9	13.3	1 X 300	3	11	2.3kg		3/8	3/8	395	296	505
CPUT2155GK	NT2155GK	14.5	1 PH	2.6	20	1 X 254	3	11	1.2kg		1/4	3/8	340	296	465
CPUT6217GK	NEK6217GK	14.5	1 PH	5.1	22	1 X300	3	13	2.3kg		3/8	1/2	395	346	518
CPUT6220GK	NT6220GK	17.4	1 PH	5.6	26.5	1 X 300	4	14	2.3kg		3/8	1/2	395	371	518
CPUT2168GK	NT2168GK	17.4	1 PH	3.3	18	1 X 254	4	11	1.2kg		1/4	3/8	340	296	465
CPUT6215Z	NT6215Z	20.4	1 PH	5.3	21										
CPUNT2178GK	NT2178GK	20.4	1 PH	3.3	18	1 X 254	4	11	1.2kg		1/4	3/8	340	296	465
CPUJ9226GK	J9226GK	21.7	1 PH	6.4	27.5	1 X 300	4	14	2.3kg		3/8	5/8	503	371	600
CPUJ9226GK/2	J9226GK	21.7	1 PH	6.4	27.5	2 X 250	4	13	2.3kg		3/8	5/8	612	346	440
CPUJ6220Z	J6220Z	25.8	1 PH	6.6	35										
CPUJ2192GK	J2192GK	26	1 PH	4.9	26	1 X 300	3	13	2.3kg		3/8	1/2	410	346	477
CPUJ9232GK	NJ9232GK	26.1	1PH	7.8	36	1X 300	4	16	4kg		1/2	5/8	503	371	600
CPUJ9232GK/2	NJ9232GK	26.1	1PH	7.8	36	2 X300	2	13	2.3kg		1/2	5/8	612	346	440
CPUJ9238GK	NJ9238GK	32.7	1PH	10.1	43	1X350	4	16	4kg		1/2	jn	530	445	600
CPU9238GK/2	NJ9238GK	32.7	1PH	10.1	43	2X300	4	13	2.3kg		3/8	5/8	783	346	460
CPUJ6226Z	J6226Z	34.4	1 PH	6.6	31										
CPU2212GK	J2212GK	34.4	1 PH	6.1	36	1 X 300	4	13	2.3kg		3/8	1/2	410	346	477

CPU SERIES -Copeland/Manuope Technical Data

Technical Data

Unit Model	Compressor Details					Condenser Details				Receiver Cap	Consections Solder		Dimensions (mm)		
	Model	Disp	Phase	F.L.A	L.R.A	No. Fans	Phase	R.L.A	Liquid		Suction	Lth	Dth	Ht	
CPU10MT-1	CS10K6E-PFJ-551	38.1	1PH	10.1	55	1X 350	1PH		2.5KG	3/8	3/4	580	765	450	
CPU10MT-3	CS10K6E-TFD-551	38.1	3PH	4.2	27	1 X 350	1PH		2.5KG	3/8	3/4	580	765	450	
CPU14MT-1	CS14K6E-PFJ-551	48.6	1PH	12.5	58	1 x 400	1PH		4.4KG	3/8	3/4	580	765	650	
CPU14MT-3	CS14K6E-TFD-551	48.6	3PH	4.7	28	1 x 400	1PH		4.4KG	3/8	3/4	580	765	650	
CPU18MT-1	CS18K6E-PFJ-551	61.4	1PH	13.6	64	1 x400	1PH		4.4KG	3/8	3/4	580	765	650	
CPU18MT-3	CS18K6E-TFD-551	61.4	3PH	4.7	33	1 x400	1PH		4.4KG	3/8	3/4	580	765	650	
CPU20MT	CS20K6E-TFD-551	74.3	3PH	5.1	40	2 x350	1PH		4.4KG	1/2	3/4	1065	800	450	
CPU27MT	CS27K6E-TFD-551	92.4	3PH	8.5	41	2 X 400	1PH		6.6KG	1/2	7/8	1085	800	650	
CPU33MT	CS33K6E-TFD-551	106.2	3PH	9.9	45	2 X 400	1PH		6.6KG	1/2	7/8	1085	800	650	
CPU65MT	MTZ65-4VI	107.7	3PH	8.1	64	2 x400	1PH		8 KG	1/2	7/8	1065	800	650	
CPUMT73	MTZ73-4VI	120.94	3PH	8.8	80	2 x 400	1PH		8 KG	1/2	7/8	1065	800	650	
CPUMT81	MTZ81-4VI	135.98	3PH	9.7	80	2 x 450	1PH		8 KG	1/2	1 1/8	1270	800	900	
CPUMT100	MTZ100-4VI	171.26	3PH	12.9	78	2 x450	1PH		14.0KG	1/2	1 1/8	1270	800	900	
CPUMT125	MTZ125-4VI	215.44	3PH	14.4	105	2 x450	1PH		14.0KG	1/2	1 1/8	1270	800	900	
CPUMT144	MTZ144-4VI	241.87	3PH	19.36	115	2 x 500	1PH		14.0KG	5/8	1 3/8	1670	965	950	
CPUMT160	MTZ160-4VI	271.55	3PH	20.2	130	2 x500	3PH		14.0KG	5/8	1 3/8	1670	965	950	